SUNLITE

Product Number: SL041005

Product Name	Halogen-Free Flame-Retardant Vibration Damper

Primary material	IIR+aluminum foil
Specifications	Customised services
Performance indicators	Composite Loss Factor: ⩾0.2 Density Range: 1.0–2.3 g/cm³ (adjustable) Flame Retardancy: UL94 V0, EN45455 R2 Operating Temperature Range: -40°C to +120°C Application Temperature Range: 0°C to 50°C Ageing Performance: Adhesive strength and flexibility remain excellent after 72 hours of thermal ageing Adhesion Performance: Strong adhesive backing ensures no edge lifting or blistering after bonding
Product Features	Flame-retardant and halogen-free, highly effective noise reduction and vibration damping, weather-resistant and durable, high conformability, easy installation.
Fields of application	Interior door panels, boot and wheel arch areas, engine compartment and front bulkhead, roof or side wall structures, and other vehicle structural components.
Customised Services	Dimensions, materials and colours can be customised to meet customer requirements.

The contents of this product information sheet are for reference only. For detailed information, please consult our customer service team. The company reserves the right to modify this technical information without prior notice or consultation.

E overseas@sunlitetek.com W www.sunlitetek.com T +1(646)594-3222

Copyright © 2025 Guangdong Sunlite Technology Co., Ltd. All Rights Reserved.